

IR Vari-focus bullet Network Camera

Product Type

IR Vari-focus bullet Network Camera

Product Model

BSR-IM2210-B1001



Key Features

- ✧ 1.3MP (1280×960) high resolution
- ✧ 120 dB WDR
- ✧ Smart video detection
- ✧ Smart focus
- ✧ Support 1-ch audio I/O, 1-ch alarm I/O(Optional)
- ✧ Built-in Micro SD/SDHC card slot (Optional)
- ✧ Analoga Output(Optional)



Specifications

Parameters/Model		BSR-IM2210-B1001
Camera	Image Sensor	1/3" Progressive Scan CMOS
	Min. Illumination	0.1Lux@(F1.2), AGC ON, 0 Lux with IR
	Shutter Time	1/25s--1/10,000s
	Lens	2.8-12mm@F1.4

Parameters/Model		BSR-IM2210-B1001
	Lens Mount	φ14
	Auto Iris	DC Drive
	Digital Noise Reduction	3D DNR
	Wide Dynamic Range	120 dB
	Day & Night	IR cut filter with auto switch
Compression Standard	Video Compression	H.264/MJPEG
	H.264 Codec Profile	Main Profile
	Bit Rate	64Kbps—8Mbps
	Audio Compression	G.711/G.722.1/G.726/MP2L2(Optional)
	Dual Stream	Yes
Image	Max. Image Resolution	1280×960
	Frame Rate	30fps(1280×960) 25fps(1280×720)
	Image Settings	Saturation, brightness, contrast, sharpness adjustable through client software or browser
	BLC	Yes, zone configurable
	Video Active Enhancement	Yes
Network	Alarm Trigger	Motion detection, abnormality alarm, video block alarm
	Protocols	TCP/IP , RTP , UDP , HTTP , DHCP , DDNS , PPPoE , NTP
	System Compatibility	ONVIF
Interface	Communication Interface	1 RJ45 10M/100M Ethernet Interface
	On-board storage	Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB
General	Operation Conditions	-10°--55°; humidity 95% or less
	Power Supply	12VDC ±10% ; PoE(802.3af)
	Power Consumption	Max.5W
	Impact Protection	IK 10
	Ingress Protection	IP66
	IR Range	30m
	Dimensions	147(Φ)mm*123mm(H)
	Weight	1200g

Typical Applications

Suitable for financial, military, prisons, airports, factories, government, hotels, such as IP monitoring, especially suitable for the night, such as outdoor, warehouses and other locale with auxiliary infrared light source.

Picture



Dimensions

